

THERMIC FLUID HEATING SYSTEM (HOT OIL CIRCULATION SYSTEM)



EXPANSION TANK : 20 LTR. TO 5000 LTR. (OR AS PER REQUIRED)

MAKE-UP TANK : 20 LTR. TO 3000 LTR. (OR AS PER REQUIRED)



ELECTRICALLY OPERATED

CAPACITY : 5,000 Kcal. TO 3,00,000 Kcal. (3 KW TO 400 KW)

COMPACT DESIGN USED ALSO LAB. PURPOSE, SKID MOUNTED TROLLEY TYPE MOVABLE

EXPANSION TANK SHIFT LOSE FOR MOUNTING AT THE HIGHEST POINT IN THE PIPING SYSTEM (OPTIONAL)

THYRISTOR (SCR) CONTROL (OPTIONAL)

OPTIONAL COOLING THROUGH THE SAME HEATING MEDIA

TEMP. : -30 °C. TO +325 °C.

EX-PROOF IIA, IIB & IIC (OPTIONAL)

UNIT - I & REG. OFFICE :

54/4 , G.I.D.C. ESTATE, MAKARAPURA, BARODA –390010, GUJARAT, INDIA.

TEL : 91-265-2658711,22. TELEFAX : 0265 – 2633835

MOB. : 09824060315

UNIT II

PLOT NO.573, 574 ,591, 592 GIDC, PO. ALINDRA, MANJUSAR – 391775, SAVLI, DIST. BARODA.INDIA.

TEL. : 02667 –292952

Mail : sales@sensewellindia.com

Web. : www.sensewellindia.com
